



**FRESENIUS
KABI**

caring for life



Smart Holder COM

Holder for power supply, nurse call and IT connectivity

Integrated AC/DC adapter

Immediate release of the pump

Simple power cable connection

Nurse call cable connection

Serial communication for IT connectivity

LED for power status

Grooved surface to facilitate cleaning

Safety thread guides to avoid unexpected disconnection

Smart Holder COM

Pump compatibility

- Amika
- Amika+

Power supply

Holder input

- AC input voltage: 100-240 Vac
- AC input frequency: 50/60 Hz
- AC input current: 110 mA-205 mA

Holder output

- 9 Vdc +/- 5 % / 9 W (maximum load)

Swinglock clamp

- Versatile clamp that allows the fixation on a rail or on a pole
- Pole diameter: 8 mm to 40mm
- Rail dimensions: 10 mm to 35mm

Dimensions (H/W/D) / Weight

- Dimensions: 132 x 118 x 46 mm (without clamp)
- Weight: approximately 0.45 kg

Operating conditions

- Temperature: 10°C to 40°C
- Pressure: 700hPa to 1060hPa
- Humidity: 30% to 85%
- Altitude: less than 3000m

Storage conditions

- Temperature: -20°C to +45°C
- Pressure: 500hPa to 1060hPa
- Humidity: 10% to 90%



Nurse call specifications

- Input/output: 24 Vdc SELV(Safety Extra Low Voltage)/ 0.5 A maximum 24 Vac / 0.5 A maximum
- Electrical insulation: 1.5 kV insulation
- System type: Electrical analogical system
- Compatibility: Compatible with 3 wires contacts. Relay type, dry contacts stand-off / work contact - positive / negative polarity option
- Compliance with standards: IEC/EN 60601-1 (leakage current)

RS232 serial communication connector specifications

- Mini USB port
- Input/output: RS232 signal
- Electrical insulation: 1.5 kV insulation
- Compliance with standards: IEC/EN 60601-1 (leakage current)

Compliance with standards

- Conform to Medical Device Regulation (EU) 2017/745
- Safety of ElectroMedical Equipments: conform to EN/IEC 60601-1, EN/IEC 60601-1-6, EN/IEC 60601-1-11
- EMC: conform to EN/IEC 60601-1-2
- Labeling: conform to EN 1041, EN ISO/ISO 15223-1
- Protection against moisture (Holder): IP32 - drip-protected
- Defibrillation-proof type CF applied part 
- Class II equipment 

Note: the full list of applicable standards is available upon request
The device is protected against leakage current and does not disturb ECG or EEG devices

Amika is a registered trademark by Fresenius Kabi in selected countries. Due to our policy of continuous product development as well as changes in standards, the features described are subject to change or not available in your country. This medical device is regulated by health authorities and is CE according to Medical Device Regulation (EU) 2017/745. Please contact your Fresenius Kabi representative for more details. Pictures are not contractual.